

Minimodel No. Sunny A18 Soft Serve Freezer

Counter top, single flavor, gravity feed

Offer all popular soft serve from low or non-fat ice creams to custard, frozen yogurt, and sorbet with compact, single dispenser design; the low noise operation and electric current control ensure optimal texture and taste ideal for convenience store environment.





Product customization may be available upon request




Minimum Clearance should be 300mm on left, right, and rear for assuring adequate air flow



One dedicated electrical connection is required. Check with local electrician for cord and receptacle specifications if 50 Hz or 60 Hz Equipment is desired

Sunny A18





Weight	lbs.	kgs.	
Net	262	107	
Total	322	139	
Dimensions	in.	mm.	
Width	13.6	347	
Depth	27.6	700	
Height	31.9	810	
Electrical	Maximum Fuze Size	Minimum Ampacity	Poles(P) Wires(W)

These specifications are subject to change without notice as further research and development efforts continuously improve the model.

10

10

2P 3W

2P 3W

35

35

Shenzhen Oceanpower Ecological Food Science and Technology Co., Ltd. Add: Block C&D, 7&8/F, Bldg. F3.8, Tian'an Cyber Park, Chegongmiao,

Shenzhen, China Phone: 86-75583897272 Email: info@oceanpower.com

220-240/50/1

220-240/60/1

Technical data

Model	Power
Sunny A18	1000W
Flavors	Main Compressor
single	0.75HP
Production Capacity	Cooling System
18L/H	Air Cooled
Mix Hopper	Refrigerant
6.5L	R404A
Cylinder	Options
2L	Cone Dispenser

Function illustration

Microprocessor Regulation

Regulates the entire refrigeration process and maintains consistent product viscosity, adjustable through modifying viscosity between level 1 and level 8 on the front panel.

Safety Protection

Shuts down for self-protection when motor overload or compressor overheat occurs due to power surge or abnormal voltage from power supply.

Mix low alarm

The low liquid alarm will sound when the hopper is lack of ice cream mix.

Dispensing Counter

The number of ice creams dispensed is displayed on the front panel each time the discharge handle is pressed.

Standby Mode

The machine automatically enters standby mode after two hours of inactivity and will resumes normal operation after any keys or handles are pressed.

Low Noise Operation

The revolutionary worm gear reducer, together with import three-phase beater motor, greatly reduces operating noise.

